

Product Specifications – Leveluk Kangen 8



The Kangen® 8 is Enagic®'s most powerful antioxidant machine – featuring 8 platinum-dipped titanium plates for improved water ionization and increased antioxidant production potential. Enjoy this Kangen Water® machine in virtually any country, thanks to its worldwide multi-voltage power supply and interchangeable plug capability (sold separately). If you're looking for a powerful, versatile, feature-loaded machine, the Kangen® 8 is for you.

Generates: Strong Kangen Water (11.0pH), Kangen Water® (8.5 – 9.5pH), Neutral Water (7.0pH), Slightly Acidic “Beauty” Water (4.0 – 6.0pH), and Strong Acidic Water (2.5pH)

Product Specifications

Model name / number	Leveluk Kangen 8 / A26-00
Languages	8 Language Display & Audio
Water source connection	1-way diverter (TAP/ION) connects to the end of faucet
Power Supply	100-240V AC 50/6-Hz 2.6 – 1.1A Worldwide Multi-Voltage Power Supply, with Interchangeable Plug Capability
Power consumption	Energy Saving – Low Input, High Output Approx. 230W (under maximum electrolysis function)
System	Continuous Ionized Electrolysis Water Generator System (with built-in flow rate sensor)
Production rate (gallons(s)/minute)	<ul style="list-style-type: none"> ○ Kangen Water®: 1.2-2.0 ○ Acidic water: 0.4-0.7 ○ Strong Acidic water: 0.16-0.3
Level Selections	<ul style="list-style-type: none"> ○ Kangen Water® / 3 levels (approx. pH 8.5-9.5) ○ Clean water (pH 7) ○ Acidic water (approx. pH 5.5-6.5) ○ Strong Acidic water (approx. pH 2.4-2.7)

	<ul style="list-style-type: none"> ○ Strong Kangen water (approx. pH 11.0)
Electrolysis Capability (continuous use)	Approx. 30 min at normal room temperature
Cell cleaning method	10 Second Automatic Cleaning with On-Screen E-Cleaning Instructions
Applicable water quality and pressure	Municipally supplied drinking water: dynamic range in 50kpa – 500kpa
Electrolysis Enhancer	Forced dissolving type additive system (One time addition produces approx. 1.0-1.3 gallons of Strong Acidic water.)
Enhancer Refilling	Indicates by voice, buzzer and LCD
Protector	Current Limiter/Voltage Stabilizer/Thermal Protection
Electrode material	Platinum coated Titanium
Electrode plates	8

Water Filtering

Filtering medium	Anti-bacterial Granular Activated Charcoal and Sulfurous Acidic Calcium
Residual chlorine removal	Total water flow: 1,500 gallons Removal rate / JISS3201 Test: 80%
Initial chlorine removal	95% or greater
Elements not removable	Metallic ions and/or salinity present in original tap water
Time to exchange the filter	Automatic Filter Sensor – No More New Filter Reset! When the filter has treated 1500 gallons of water (depends on quality of original tap water)
Optional/replacement parts	<ul style="list-style-type: none"> ○ F8 High grade water filter ○ Calcium Lactate: 3g x 12 packs/box ○ Electrolysis enhancer: 3 bottles of 0.93pt ○ Cleaning filter: E-Cleaner

Additional Info

Dimensions	345 x 279 x 147 (mm)
Gross Weight (wet)	5 kg